

# Rhinofloor Contract Acoustic

Characteristic	Standard	Units	Value
Type of Flooring	EN651		Heterogeneous PVC Floor Covering
Rhinogrip			Yes
Pattern			Printed
<b>Safety Criteria</b>			
Flammability	EN 13501-1	Class	Bfl-s1 Loose Laid
Slip Resistance	EN 13893	Class	DS
Slip Resistance	DIN 51130	group	R10
Impact Sound Reduction	ISO 140-8	dB	18
<b>General Properties</b>			
Sheet Width	EN 426	m	2, 3, 4
Sheet Length	EN 426	m	15 - 30
Overall Thickness	EN 428	mm	3.00
Thickness of wear layer	EN 429	mm	0.5
Total weight	EN 430	Kg/m <sup>2</sup>	2.37
Residual indentation	EN 433	mm	≤ 0.2
Colour fastness	ISO 105-B02	Rating	≥ 6
Wear group	EN 649		T
Thickness loss	EN 649	mm	≤ 0.08
Static Electric Charge	EN 1815	kV	≤ 2.0



Class Domestic – heavy



Class Commercial – Heavy



Class Industrial – General



EN 14041 :2004  
09

**Manufactured by:**  
Armstrong World Industries  
Teesside Industrial Estate  
Thornaby-on-Tees  
TS17 9JT U.K.



ISO 9001/ISO14001

Armstrong flooring products are to be installed in full accordance with Armstrong's installation Instructions and recognised trade standards. An effective, regular cleaning and maintenance programme is vital for retaining a high appearance level. Armstrong flooring products should only be used as floorcoverings. Note: Armstrong Floor Products reserve the right to amend this specification without giving prior notice.